R(current) **to R**(proposed) Zoning Comparison

The intent of the R zone is to preserve rural areas of the County for agriculture and other natural resource development, residential uses of a rural character, extensive recreational facilities, and protection of scenic and environmentally sensitive areas.



Existing development in the Rural zone



Illustrative Depiction of Standards for Detached House Building Type



Side Section of Structure (Principal Building)

Height is proposed to be measured from the average grade to the mean height level between eaves and ridge of a gable, hip, mansard, or gambrel roof or to the highest point of roof surface of a flat roof.



Standard Method of Development for Detached House Building Type

	R (current)	R (proposed)
Lot Area (min)	5 acres	5 acres
Density (units/acre)	1/5	1/5
Lot Width (min)		
At front building line	300'	300'
At front lot line	25'	25'
B. Placement		
Principal Building (min)		
Front setback	50'	50′
Side street setback	50′	50′
Side setback	20'	20′
Sum of side setbacks	40'	N/A
Rear setback	35'	35′
Coverage (max)		
All roofed buildings and structures	10%	10%
C. Height		
Principal Building (max)		
Overall building height (agricultural buildings are exempt)	50'	50'
Rationale for Changes Marked	in Red	
Sum of Side Setbacks The Sum of Side Setbacks requ zone.	iirement is redund	dant in this

Accessory Structures: Rural Zones Zoning Comparison

An accessory structure is a structure, including a building, that is subordinate to and located on the same lot as a principal building, the use of which is incidental to the use of the principal building or to the use of the land. In the Rural Residential zones, the maximum footprint of an accessory building on a lot where the main building is a detached house is 50% of the footprint of the main building. Buildings for an agricultural use are exempt from this size restriction.







ZONING MONTGOMERY a project of the Montgomery County Planning Department ZoningMontgomery.org

Standard Method of Development for Detached House Building Type

Α.	Placement	R and RC (current)	R and RC (proposed)
Det	ached Accessory Structure (min)		
From	nt setback	80'	80'
Side	e street setback	50'	50'
Side setback		15'	15'
Rea	r setback	10'	15'
Cov	erage (max)		
Acc	essory structure coverage of rear yard	25%	N/A
в.	Height		
Det	ached Accessory Structure (max)		
	rall building height ricultural buildings are exempt)	50'	50'

Rationale for Changes Marked in Red

Rear Setback

The proposed zoning code increases this setback to reduce impact on abutting properties, since the allowed height for a detached accessory structure is the same as a house.

Accessory Structure Coverage of Rear Yard

The proposed zoning code removes this standard as overall building coverage controls ground cover and the size of accessory structures.

Other Dimensional Standards

For development standards regarding principal buildings, including density, lot size and coverage, see the Rural (R) and RC Zoning Comparison fact sheets.